

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number  
**WO 2005/010871 A1**

(51) International Patent Classification: **G11B 7/00**

(21) International Application Number:  
PCT/AU2004/000987

(22) International Filing Date: 23 July 2004 (23.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003903802 23 July 2003 (23.07.2003) AU

(71) Applicant (for all designated States except US): **BAND-  
WIDTH FOUNDRY PTY LTD [AU/AU]**; 102 National  
Innovation Centre, Australian Technology Park, Eveleigh,  
New South Wales 1430 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BURYAK, Alexan-  
der [AU/AU]**; 53 Coronga Crescent, Killara, New South  
Wales 2071 (AU). **KOLOSISOVSKI, Kazimir [RU/AU]**;

72 Lachlan Street, Macquarie, Australian Capital Terri-  
tory 2614 (AU). **STEPANOV, Dmitrii, Yu [RU/AU]**; 7/126  
Croydon Avenue, Croydon Park, New South Wales, 2133  
(AU).


(74) Agent: **FREEHILLS CARTER SMITH BEADLE**;  
Level 32, MLC Centre, 19-29 Martin Place, Sydney, New  
South Wales 2000 (AU).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **OPTICAL DATA CARRIER SYSTEM**



(57) Abstract: The present invention provides a method of holographically storing data as in a series of grating structures including  $m$ -level coded elements in an optical data carrier, wherein  $m \geq 2$ , the method comprising: forming a grating sampling function as a direct sum of  $N$  partial grating sampling functions, each partial grating sampling function having a phase ( $\phi_n$ ) and amplitude ( $d_n$ ), wherein each  $d_n$  has  $m$  possible values.

WO 2005/010871 A1